

# EkkOCT

## Wireless Current Measurement Sensor

Track AC current consumption in real time with EkkOCT Wireless. EkkOCT is a wireless interface for up to three standard current transformers – allowing low-cost, real-time AC current measurement from 1A to 1000A.

**Low-cost wireless current monitoring with EkkOCT**  
EkkOCT is a wireless current monitoring device that accepts up to three standard 333 mV output current transformers rated between 1A and 1000A. Thanks to its low-cost and simple installation, EkkOCT provides a rapid way of capturing power consumption trends, and enables power monitoring to be implemented where the costs of full power metering were previously prohibitive. This is particularly relevant where EkkoSoft® Critical is being used as part of an energy optimisation project, and fine-grained power usage benchmarks are required.



Monitor  
Manage  
Maximize



Current values are measured in real-time and transmitted in standard Critical Things® format for use by EkkoSoft Critical, where this current data can be combined with representative power factor and voltage information to enable an indication of power consumption. In addition, EkkOCT can provide support up to two wired temperature and humidity sensors and has an opto-isolated 12-24V AC/DC input. These can be used to gather additional data on the operating condition of power distribution hardware.

EkkOCT transmits measured data at intervals between 30 seconds and 10 minutes. Data can either be transmitted as instantaneous values, or as the average from multiple measurements spaced evenly throughout the transmit interval. Averaging data over multiple measurements ensures that any changes to measured values between transmissions are captured. EkkOCT is housed in a standard DIN rail mount enclosure and can be powered by an internal battery or from an external 12-24V AC or DC supply.

Sir Colin Campbell Building, University of Nottingham Innovation Park,  
Triumph Road, Nottingham NG7 2TU. United Kingdom.

+44(0)115 823 2664 info@ekkosense.com www.ekkosense.com



## Critical Things®

INTEGRATED SENSOR TECHNOLOGY

PARAMETER	VALUE
Operating temperature range (EkkoAir unit)	0°C to 40°C (32°F to 104°F)
Operating humidity range (EkkoAir unit)	5% to 95% RH
Current transformer inputs	Compatible with 333mV output current transformers rated between 1A and 1000A
RF data link	GFSK 250bit/s 868.3MHz (ES-CT-10) or 923MHz (FS-CT-10)
Operating range (from EkkoHub)	> 20m (21yds)
Power Supply	12V to 24V AC or DC or internal battery
Internal battery (if not powered externally)	Replaceable LS14500 AA size Lithium Thionyl Chloride
Battery life	> 3 years (transmitting once every two minutes an average of measurements at 30s intervals)
Measuring temperature range (with optional external sensors)	0°C to 60°C (32°F to 140°F)
Measuring humidity range (with optional external sensors)	0% to 100% RH
Temperature accuracy	±0.2°C typical (±0.4°F)
Relative Humidity accuracy	±2% typical
Housing	ABS 70mm wide (4 DIN), 74mm high, 46mm deep (2.8"x2.9"x1.8") (53.5mm/2.1" including DIN rail)
Sensors	30mm (1.2") diameter, 10mm (0.4") deep, supplied with 3m (118") cable
Antenna connection	SMA female connector
Sensor, power and CT connections	Screw terminals

Sir Colin Campbell Building, University of Nottingham Innovation Park,  
 Triumph Road, Nottingham NG7 2TU. United Kingdom.

